

BALL LOCK ZIGZAG TIE UNCOATED



Application

- Used where extensive vibration is there & positive locking is required



Key Industries

- Aerospace ● Chemicals & Refineries ● Dairy & Food Processing ● Oil, Gas & Offshore ● Ship & Marines ● Solar ● Telecom ● Utility ● Windmill

Specification

Material:	Stainless Steel SS 316, SS 304
Operating Temp:	-80°C to +538°C
Installation:	By hand or with the help of tool STT1, STT2
Test Certificate:	
Packing:	100 pcs bag
Unit:	100 Pcs/Pkt

Features

- Modified wave form clamps where no other steel ties retain tension
- Grips firmly on solid object at low applied forces
- Smooth edges of ties provide utmost safety while installation

Dimension In MM				Dimension In Inch				Loop Tensile Strength (kgs)/(lbs)	G.W. /100 pcs (Kgs)/(Lbs)	Cat. No. SS 316	Cat No. SS 304
Length	Width	Thickness	Max. Bundle Dia	Length	Width	Thickness	Max. Bundle Dia				
200	4.6	0.25	50	7.87	0.18	0.01	1.97	60 (132)	0.25 (0.56)	BLZ-200	BLZ-200/4
360	4.6	0.25	100	14.17	0.18	0.01	3.94	60 (132)	0.40 (0.88)	BLZ-360	BLZ-360/4
520	4.6	0.25	150	20.47	0.18	0.01	5.91	60 (132)	0.55 (1.21)	BLZ-520	BLZ-520/4
680	4.6	0.25	200	26.77	0.18	0.01	7.87	60 (132)	0.69 (1.53)	BLZ-680	BLZ-680/4
840	4.6	0.25	250	33.07	0.18	0.01	9.84	60 (132)	0.84 (1.86)	BLZ-840	BLZ-840/4
1000	4.6	0.25	300	39.37	0.18	0.01	11.81	60 (132)	0.99 (2.18)	BLZ-1000	BLZ-1000/4
200	7.9	0.25	50	7.87	0.31	0.01	1.97	170 (375)	0.47 (1.05)	BLHZ-200	BLHZ-200/4
360	7.9	0.25	100	14.17	0.31	0.01	3.94	170 (375)	0.73 (1.60)	BLHZ-360	BLHZ-360/4
520	7.9	0.25	150	20.47	0.31	0.01	5.91	170 (375)	0.98 (2.16)	BLHZ-520	BLHZ-520/4
680	7.9	0.25	200	26.77	0.31	0.01	7.87	170 (375)	1.23 (2.72)	BLHZ-680	BLHZ-680/4
840	7.9	0.25	250	33.07	0.31	0.01	9.84	170 (375)	1.48 (3.28)	BLHZ-840	BLHZ-840/4
1000	7.9	0.25	300	39.37	0.31	0.01	11.81	170 (375)	1.74 (3.83)	BLHZ-1000	BLHZ-1000/4