

# COLORED CABLE TIES



## Application

For wire identification in electrical installation and for identification of production bags in chemical & pharma industries



## Key Industries

- Chemicals & Refineries
- Dairy & Food Processing
- Drug & Pharma

## Specification

<b>Material:</b>	Nylon 66
<b>Color:</b>	All colors are available
<b>Operating Temp:</b>	-40°C to +185°C
<b>Flammability Rating:</b>	UL 94V-2
<b>Installation:</b>	By hand or tool
<b>Test Certificate:</b>	
<b>Packing:</b>	100 pcs bag in all sizes & 1000 pcs. bag upto 200mm length
<b>Unit:</b>	100 Pcs/Pkt & 1000 Pcs/K

## Features

- Colored ties ensures easy identification of wires batch wise production bags

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs(lbs)	Maxi. Bundle Dia (mm)	Color	
						100 pcs pack (PKT)	1000 pcs pack (K)
75	2.5	1.10	3.0	8 (18)	12	SL-75GN	SL-75KGN
75	2.5	1.10	3.0	8 (18)	12	SL-75BE	SL-75KBE
75	2.5	1.10	3.0	8 (18)	12	SL-75YW	SL-75KYW
75	2.5	1.10	3.0	8 (18)	12	SL-75RD	SL-75KRD
104	2.5	1.10	4.1	8 (18)	22	SL-100GN	SL-100KGN
104	2.5	1.10	4.1	8 (18)	22	SL-100BE	SL-100KBE
104	2.5	1.10	4.1	8 (18)	22	SL-100YW	SL-100KYW
104	2.5	1.10	4.1	8 (18)	22	SL-100RD	SL-100KRD
104	2.5	1.10	4.1	12 (27)	22	SL-100XGN	SL-100XKGN
104	2.5	1.10	4.1	12 (27)	22	SL-100XBE	SL-100XKBE
104	2.5	1.10	4.1	12 (27)	22	SL-100XYW	SL-100XYW
104	2.5	1.10	4.1	12 (27)	22	SL-100XRD	SL-100XKRD
120	2.5	1.10	4.7	8 (18)	27	SL-120GN	SL-120KGN
120	2.5	1.10	4.7	8 (18)	27	SL-120BE	SL-120KBE
120	2.5	1.10	4.7	8 (18)	27	SL-120YW	SL-120KYW
120	2.5	1.10	4.7	8 (18)	27	SL-120RD	SL-120KRD
150	2.5	1.10	5.9	8 (18)	35	SL-150GN	SL-150KGN
150	2.5	1.10	5.9	8 (18)	35	SL-150BE	SL-150KBE
150	2.5	1.10	5.9	8 (18)	35	SL-150YW	SL-150KYW
150	2.5	1.10	5.9	8 (18)	35	SL-150RD	SL-150KRD
204	3.6	1.45	8.0	18 (40)	53	SL-200IGN	SL-200IKGN
204	3.6	1.45	8.0	18 (40)	53	SL-200IBE	SL-200IKBE
204	3.6	1.45	8.0	18 (40)	53	SL-200IYW	SL-200IKYW
204	3.6	1.45	8.0	18 (40)	53	SL-200IRD	SL-200IKRD
250	3.6	1.45	9.8	18 (40)	68	SL-250IGN	
250	3.6	1.45	9.8	18 (40)	68	SL-250IBE	
250	3.6	1.45	9.8	18 (40)	68	SL-250IYW	
250	3.6	1.45	9.8	18 (40)	68	SL-250IRD	
300	3.6	1.45	11.8	18 (40)	80	SL-300IGN	
300	3.6	1.45	11.8	18 (40)	80	SL-300IBE	
300	3.6	1.45	11.8	18 (40)	80	SL-300IYW	
300	3.6	1.45	11.8	18 (40)	80	SL-300IRD	
368	3.6	1.45	14.5	18 (40)	104	SL-368IGN	

# COLORED CABLE TIES



Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs(lbs)	Maxi. Bundle Dia (mm)	Color	
						100 pcs pack (PKT)	1000 pcs pack (K)
368	3.6	1.45	14.5	18 (40)	104	SL-368IBE	
368	3.6	1.45	14.5	18 (40)	104	SL-368IYW	
368	3.6	1.45	14.5	18 (40)	104	SL-368IRD	
200	4.8	1.50	8.0	30 (67)	53	SL-200SXGN	SL-200SXKGN
200	4.8	1.50	8.0	30 (67)	53	SL-200SXBE	SL-200SXKBE
200	4.8	1.50	8.0	30 (67)	53	SL-200SXYW	SL-200SXKYW
200	4.8	1.50	8.0	30 (67)	53	SL-200SXRD	SL-200SXKRD
204	4.8	1.50	8.0	22 (49)	53	SL-200SGN	SL-200SKGN
204	4.8	1.50	8.0	22 (49)	53	SL-200SBE	SL-200SKBE
204	4.8	1.50	8.0	22 (49)	53	SL-200SYW	SL-200SKYW
204	4.8	1.50	8.0	22 (49)	53	SL-200SRD	SL-200SKRD
254	4.8	1.50	10.0	22 (49)	68	SL-250SGN	SL-250SKGN
254	4.8	1.50	10.0	22 (49)	68	SL-250SBE	SL-250SKBE
254	4.8	1.50	10.0	22 (49)	68	SL-250SYW	SL-250SKYW
254	4.8	1.50	10.0	22 (49)	68	SL-250SRD	SL-250SKRD
315	4.8	1.50	12.4	22 (49)	86	SL-300SGN	
315	4.8	1.50	12.4	22 (49)	86	SL-300SBE	
315	4.8	1.50	12.4	22 (49)	86	SL-300SYW	
315	4.8	1.50	12.4	22 (49)	86	SL-300SRD	
373	4.8	1.50	14.7	22 (49)	104	SL-368SGN	
373	4.8	1.50	14.7	22 (49)	104	SL-368SBE	
373	4.8	1.50	14.7	22 (49)	104	SL-368SYW	
373	4.8	1.50	14.7	22 (49)	104	SL-368SRD	
455	4.8	1.50	17.9	22 (49)	130	SL-450SGN	
455	4.8	1.50	17.9	22 (49)	130	SL-450SBE	
455	4.8	1.50	17.9	22 (49)	130	SL-450SYW	
455	4.8	1.50	17.9	22 (49)	130	SL-450SRD	
550	4.8	1.50	21.7	22 (49)	165	SL-550SGN	
550	4.8	1.50	21.7	22 (49)	165	SL-550SBE	
550	4.8	1.50	21.7	22 (49)	165	SL-550SYW	
550	4.8	1.50	21.7	22 (49)	165	SL-550SRD	
206	7.8	1.80	8.1	54 (119)	53	SL-200HGN	
206	7.8	1.80	8.1	54 (119)	53	SL-200HBE	
206	7.8	1.80	8.1	54 (119)	53	SL-200HYW	
206	7.8	1.80	8.1	54 (119)	53	SL-200HRD	
256	7.8	1.80	10.1	54 (119)	68	SL-250HGN	
256	7.8	1.80	10.1	54 (119)	68	SL-250HBE	
256	7.8	1.80	10.1	54 (119)	68	SL-250HYW	
256	7.8	1.80	10.1	54 (119)	68	SL-250HRD	
312	7.8	1.80	12.3	54 (119)	82	SL-300HGN	
312	7.8	1.80	12.3	54 (119)	82	SL-300HBE	
312	7.8	1.80	12.3	54 (119)	82	SL-300HYW	
312	7.8	1.80	12.3	54 (119)	82	SL-300HRD	
382	7.8	1.80	15.0	54 (119)	105	SL-380HGN	
382	7.8	1.80	15.0	54 (119)	105	SL-380HBE	
382	7.8	1.80	15.0	54 (119)	105	SL-380HYW	
382	7.8	1.80	15.0	54 (119)	105	SL-380HRD	
453	8.1	1.95	17.8	54 (119)	130	SL-450HGN	
453	8.1	1.95	17.8	54 (119)	130	SL-450HBE	
453	8.1	1.95	17.8	54 (119)	130	SL-450HYW	
453	8.1	1.95	17.8	54 (119)	130	SL-450HRD	
551	9.1	2.00	21.7	81 (180)	163	SL-550HGN	
551	9.1	2.00	21.7	81 (180)	163	SL-550HBE	
551	9.1	2.00	21.7	81 (180)	163	SL-550HYW	
551	9.1	2.00	21.7	81 (180)	163	SL-550HRD	
616	9.1	2.00	24.3	81 (180)	180	SL-610HGN	
616	9.1	2.00	24.3	81 (180)	180	SL-610HBE	
616	9.1	2.00	24.3	81 (180)	180	SL-610HYW	
616	9.1	2.00	24.3	81 (180)	180	SL-610HRD	
716	9.1	2.00	28.2	81 (180)	210	SL-710HGN	
716	9.1	2.00	28.2	81 (180)	210	SL-710HBE	
716	9.1	2.00	28.2	81 (180)	210	SL-710HYW	
716	9.1	2.00	28.2	81 (180)	210	SL-710HRD	
816	9.1	2.00	32.1	81 (180)	240	SL-810HGN	
816	9.1	2.00	32.1	81 (180)	240	SL-810HBE	
816	9.1	2.00	32.1	81 (180)	240	SL-810HYW	
816	9.1	2.00	32.1	81 (180)	240	SL-810HRD	

# COLORED CABLE TIES



Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs(lbs)	Maxi. Bundle Dia (mm)	Color	
						100 pcs pack (PKT)	1000 pcs pack (K)
916	9.1	2.00	36.1	81 (180)	276	SL-910HGN	
916	9.1	2.00	36.1	81 (180)	276	SL-910HBE	
916	9.1	2.00	36.1	81 (180)	276	SL-910HYW	
916	9.1	2.00	36.1	81 (180)	276	SL-910HRD	
1016	9.1	2.00	40.0	81 (180)	305	SL-1010HGN	
1016	9.1	2.00	40.0	81 (180)	305	SL-1010HBE	
1016	9.1	2.00	40.0	81 (180)	305	SL-1010HYW	
1016	9.1	2.00	40.0	81 (180)	305	SL-1010HRD	

**Tolerance Dimension (mm):** Length -  $\pm 1$  to 5, Width -  $\pm 0.3$  to 0.4, Thickness -  $\pm 0.2$  to 0.4