

# DUAL LOCKING PCB SUPPORT SPACER

## Application

- This supports are made to use between PCB to PCB or PCB to chassis as a spacer



## Key Industries

Electrical/Electronics • White Goods & Appliances

## Specification

|                        |                    |
|------------------------|--------------------|
| <b>Material:</b>       | Nylon 66, UL 94V-2 |
| <b>Color:</b>          | Natural            |
| <b>Operating Temp:</b> | -40°C to +85°C     |
| <b>Packing:</b>        | 100 Pcs. bag       |
| <b>Unit:</b>           | 100 Pcs/Pkt        |

## Features

- Barbed arrow mounts on both ends locking securely

| A Spacing Height (mm) | C mm | Cat No. |
|-----------------------|------|---------|
| 4.8                   | 5.25 | PBD-4   |
| 6.4                   | 5.25 | PBD-6   |
| 9.6                   | 5.25 | PBD-9   |
| 12.7                  | 5.30 | PBD-13  |
| 15.9                  | 4.85 | PBD-16  |
| 19.1                  | 4.90 | PBD-19  |
| 22.1                  | 4.85 | PBD-22  |
| 28.2                  | 4.90 | PBD-28  |

Tolerance Dimension (mm):-  
Spacing Height -  $\pm 0.2$  to 1, C -  $\pm 0.2$  to 1