

EASY LOCK STEEL TIE UNCOATED



Application

- Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement

Key Industries

- Aerospace • Chemicals & Refineries • Dairy & Food Processing • Oil, Gas & Offshore • Ship & Marines • Solar • Telecom • Utility • Windmills



Specification

Material:	Stainless Steel SS 316, SS 304
Operating Temp:	-80°C to +538°C
Installation:	By tie tools (STT 4) & hook (STT 3)
Test Certificate:	
Packing:	100 pcs bag in all sizes
Unit:	100 Pcs/Pkt

Features

- Easy lock steel ties are self locking with multiple locking systems designed for fast, strong and secure installation
- Smooth edges of ties provide utmost safety while installation

Dimension In MM				Dimension In Inch				Loop Tensile Strength (Kgs)/(lbs)	G.W. /100 pcs (Kgs)/(Lbs)	Cat. No. SS 316	Cat No. SS 304
Length	Width	Thickness	Max. Bundle Dia	Length	Width	Thickness	Max. Bundle Dia				
150	7.0	0.25	35	5.91	0.28	0.01	1.38	45 (99)	0.23 (0.50)	EL-150	EL-150/4
200	7.0	0.25	51	7.87	0.28	0.01	2.01	45 (99)	0.29 (0.63)	EL-200	EL-200/4
225	7.0	0.25	60	8.86	0.28	0.01	2.36	45 (99)	0.31 (0.68)	EL-225	EL-225/4
250	7.0	0.25	65	9.84	0.28	0.01	2.56	45 (99)	0.33 (0.72)	EL-250	EL-250/4
300	7.0	0.25	80	11.81	0.28	0.01	3.15	45 (99)	0.41 (0.90)	EL-300	EL-300/4
360	7.0	0.25	100	14.17	0.28	0.01	3.94	45 (99)	0.48 (1.05)	EL-360	EL-360/4
450	7.0	0.25	125	17.72	0.28	0.01	4.92	45 (99)	0.57 (1.25)	EL-450	EL-450/4
600	7.0	0.25	175	23.62	0.28	0.01	6.89	45 (99)	0.74 (1.63)	EL-600	EL-600/4
610	7.0	0.25	180	24.02	0.28	0.01	7.09	45 (99)	0.77 (1.69)	EL-610	EL-610/4
750	7.0	0.25	225	29.53	0.28	0.01	8.86	45 (99)	0.94 (2.07)	EL-750	EL-750/4
1000	7.0	0.25	300	39.37	0.28	0.01	11.81	45 (99)	1.19 (2.62)	EL-1000	EL-1000/4
150	12.0	0.25	35	5.91	0.47	0.01	1.38	111 (245)	0.44 (0.97)	ELH-150	ELH-150/4
200	12.0	0.25	51	7.87	0.47	0.01	2.01	111 (245)	0.58 (1.27)	ELH-200	ELH-200/4
225	12.0	0.25	60	8.86	0.47	0.01	2.36	111 (245)	0.62 (1.36)	ELH-225	ELH-225/4
250	12.0	0.25	65	9.84	0.47	0.01	2.56	111 (245)	0.67 (1.47)	ELH-250	ELH-250/4
300	12.0	0.25	80	11.81	0.47	0.01	3.15	111 (245)	0.78 (1.71)	ELH-300	ELH-300/4
360	12.0	0.25	100	14.17	0.47	0.01	3.94	111 (245)	0.93 (2.05)	ELH-360	ELH-360/4
450	12.0	0.25	125	17.72	0.47	0.01	4.92	111 (245)	1.04 (2.29)	ELH-450	ELH-450/4
600	12.0	0.25	175	23.62	0.47	0.01	6.89	111 (245)	1.40 (3.08)	ELH-600	ELH-600/4
610	12.0	0.25	180	24.02	0.47	0.01	7.09	111 (245)	1.41 (3.10)	ELH-610	ELH-610/4
750	12.0	0.25	225	29.53	0.47	0.01	8.86	111 (245)	1.72 (3.79)	ELH-750	ELH-750/4
1000	12.0	0.25	300	39.37	0.47	0.01	11.81	111 (245)	2.30 (5.07)	ELH-1000	ELH-1000/4