

FIRE RETARDANT CABLE TIES



Application

For cable/wire bunching in fire hazardous area or in public transport where safety from fire is important



Key Industries

- Aviation • Locomotive • Oil, Gas & Offshore
- Ship & Marines

Specification

Material:	Nylon 66
Color:	Milky White
Operating Temp:	-40°C to 85°C
Flammability Rating:	UL 94V-0
Installation:	By hand or tool cat no. TT-3, TT-4, TT-5
Test Certificate:	UL & CE recognized/ROHS compliance
Packing:	100 pcs bag in all sizes & 1000 pcs. bag upto 200mm length
Unit:	100 Pcs/Pkt & 1000 Pcs/K

Features

- It is a self-locking, non-releasable, economical & versatile method of cable/wire bunching systems
- Its self extinguish property does not allow fire to travel further

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs (lbs)	Maxi. Bundle Dia (mm)	Natural 100 pcs pack Cat No.	Natural 1000 pcs pack Cat No.
75	2.5	1.10	3.0	8 (18)	12	SL-75F	SL-75KF
104	2.5	1.10	4.1	8 (18)	22	SL-100/F	SL-100K/F
104	2.5	1.10	4.1	12 (27)	22	SL-100X/F	SL-100XK/F
120	2.5	1.10	4.7	8 (18)	27	SL-120/F	SL-120K/F
150	2.5	1.10	5.9	8 (18)	35	SL-150/F	SL-150K/F
200	2.5	1.10	7.9	8 (18)	53	SL-200/F	SL-200K/F
153	3.6	1.45	6.0	18 (40)	35	SL-150I/F	SL-150IK/F
153	3.6	1.45	6.0	22 (49)	35	SL-150IX/F	SL-150IXK/F
204	3.6	1.45	8.0	18 (40)	53	SL-200I/F	SL-200IK/F
250	3.6	1.45	9.8	18 (40)	68	SL-250I/F	
300	3.6	1.45	11.8	18 (40)	80	SL-300I/F	
368	3.6	1.45	14.5	18 (40)	104	SL-368I/F	
200	4.8	1.50	8.0	30 (67)	53	SL-200SX/F	SL-200SXK/F
204	4.8	1.50	8.0	22 (49)	53	SL-200S/F	SL-200SK/F
254	4.8	1.50	10.0	22 (49)	68	SL-250S/F	
315	4.8	1.50	12.4	22 (49)	86	SL-300S/F	
373	4.8	1.50	14.7	22 (49)	104	SL-368S/F	
455	4.8	1.50	17.9	22 (49)	130	SL-450S/F	
550	4.8	1.50	21.7	22 (49)	165	SL-550S/F	
206	7.8	1.80	8.1	54 (119)	53	SL-200H/F	
256	7.8	1.80	10.1	54 (119)	68	SL-250H/F	
312	7.8	1.80	12.3	54 (119)	82	SL-300H/F	
382	7.8	1.80	15.0	54 (119)	105	SL-380H/F	
453	8.1	1.95	17.8	54 (119)	130	SL-450H/F	
551	9.1	2.00	21.7	81 (180)	163	SL-550H/F	
616	9.1	2.00	24.3	81 (180)	180	SL-610H/F	
716	9.1	2.00	28.2	81 (180)	210	SL-710H/F	
816	9.1	2.00	32.1	81 (180)	240	SL-810H/F	
916	9.1	2.00	36.1	81 (180)	276	SL-910H/F	
1016	9.1	2.00	40.0	81 (180)	305	SL-1010H/F	

Tolerance Dimension (mm): Length - ±1 to 5, Width - ±0.3 to 0.4, Thickness - ±0.2 to 0.4