

INSIDE PUSH MOUNT RELEASABLE TIE EASY RELEASE

Application

- Push mount ties are used to attach a bundle to another surface such as chassis of vehicles, AC's, coolers (White Goods).
- Used for harness assembly where there is constant vibration.



Key Industries

- Automobile • Electrical/Electronics
- White Goods & Appliances

Specification

Material:	Nylon 66
Color:	Natural/Black
Operating Temp:	-40°C to +85°C
Flammability Rating:	UL 94V-2
Installation:	By hand
Test Certificate:	
Packing:	100 pcs bag in all sizes
Unit:	100 Pcs/Pkt

Features

- Quick and simple cable mounting
- Its one piece construction design eliminates the use of screw or adhesive mounts which holds the bundles on chassis
- Push mount tie head can be easily pressed into pre-drilled hole and can hold wire bunch

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength (Kgs)/(lbs)	Maxi. Bundle Dia (mm)	For Hole Dia (mm)	CAT No. Natural	CAT No. Black
152	8.0	1.50	6.0	35 (50)	39	7-8	SLRP-150E	SLRP-150E/B
202	8.0	1.50	8.0	35(50)	55	7-8	SLRP-200E	SLRP-200E/B

Tolerance Dimension (mm): Length - ± 1 to 3, Width - ± 0.1 , Thickness - ± 0.1 , For Hole Dia - ± 0.1 to 0.5