

INSIDE PUSH MOUNT RELEASABLE TIE THUMB RELEASE

Application

- Push mount ties are used to attach a bundle to another surface such as chassis of vehicles, AC's, coolers (White Goods)
- Used for harness assembly where there is constant vibration



Key Industries

- Automobile • Electrical/Electronics
- White Goods & Appliances

Specification

Material:	Nylon 66
Color:	Natural/Black
Operating Temp:	-40°C to +85°C
Flammability Rating:	UL 94V-2
Installation:	By hand
Test Certificate:	
Packing:	100 pcs bag in all sizes
Unit:	100 Pcs/Pkt

Features

- Quick and simple cable mounting.
- Its one piece construction design eliminates the use of screw or adhesive mounts which holds the bundles on chassis
- Push mount tie head can be easily pressed into pre-drilled hole and can hold wire bunch
- Thumb release button allows to open wire bundles when changes are required

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength (Kgs)/(lbs)	Maxi. Bundle Dia (mm)	For Hole Dia (mm)	CAT No. Natural	CAT No. Black
150	7.0	1.60	5.9	22 (49)	32	6.0	SLRP-150H	SLRP-150H/B
200	7.0	1.60	7.9	22 (49)	50	6.0	SLRP-200H	SLRP-200H/B
250	7.5	1.60	9.9	22 (49)	65	6.0	SLRP-250H	SLRP-250H/B
300	7.5	1.60	11.8	22 (49)	80	6.0	SLRP-300H	SLRP-300H/B
380	7.5	1.60	15.0	22 (49)	105	6.0	SLRP-380H	SLRP-380H/B

Tolerance Dimension (mm): Length - ± 1 to 3, Width - ± 0.1 , Thickness - ± 0.2 , For Hole Dia - ± 0.1 to 0.5