

MULTI LOCK STEEL TIE UNCOATED



Application

- Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement



Key Industries

- Aerospace ● Chemicals & Refineries ● Dairy & Food Processing ● Oil, Gas & Offshore ● Ship & Marines ● Solar ● Telecom ● Utility ● Windmills

Specification

| | |
|--------------------------|--|
| Material: | Stainless Steel SS 316, SS 304 |
| Operating Temp: | -80°C to +538°C |
| Installation: | By hand, tie tools (STT1, STT2) & hook (STT 3) |
| Test Certificate: | |
| Packing: | 100 pcs bag in all sizes |
| Unit: | 100 Pcs/Pkt |

Features

- Multi lock steel ties are self locking with multiple locking systems designed for strong and secure hold
- It is designed to accommodate double wraps
- Smooth edges of ties provide utmost safety while installation

| Dimension In MM | | | | Dimension In Inch | | | | Loop Tensile Strength (kgs)/(lbs) | G.W. /100 pcs (Kgs)/(Lbs) | Cat. No. SS 316 | Cat No. SS 304 |
|-----------------|-------|-----------|-----------------|-------------------|-------|-----------|-----------------|-----------------------------------|---------------------------|-----------------|----------------|
| Length | Width | Thickness | Max. Bundle Dia | Length | Width | Thickness | Max. Bundle Dia | | | | |
| 150 | 7.0 | 0.25 | 35 | 5.91 | 0.28 | 0.01 | 1.38 | 60 (132) | 0.26 (0.57) | ML-150 | ML-150/4 |
| 225 | 7.0 | 0.25 | 60 | 8.86 | 0.28 | 0.01 | 2.36 | 60 (132) | 0.33 (0.72) | ML-225 | ML-225/4 |
| 300 | 7.0 | 0.25 | 80 | 11.81 | 0.28 | 0.01 | 3.15 | 60 (132) | 0.42 (0.92) | ML-300 | ML-300/4 |
| 450 | 7.0 | 0.25 | 125 | 17.72 | 0.28 | 0.01 | 4.92 | 60 (132) | 0.59 (1.30) | ML-450 | ML-450/4 |
| 610 | 7.0 | 0.25 | 180 | 24.02 | 0.28 | 0.01 | 7.09 | 60 (132) | 0.78 (1.71) | ML-610 | ML-610/4 |
| 150 | 12.0 | 0.25 | 35 | 5.91 | 0.47 | 0.01 | 1.38 | 130 (287) | 0.45 (0.99) | MLH-150 | MLH-150/4 |
| 225 | 12.0 | 0.25 | 60 | 8.86 | 0.47 | 0.01 | 2.36 | 130 (287) | 0.59 (1.30) | MLH-225 | MLH-225/4 |
| 300 | 12.0 | 0.25 | 80 | 11.81 | 0.47 | 0.01 | 3.15 | 130 (287) | 0.76 (1.67) | MLH-300 | MLH-300/4 |
| 450 | 12.0 | 0.25 | 125 | 17.72 | 0.47 | 0.01 | 4.92 | 130 (287) | 1.07 (2.35) | MLH-450 | MLH-450/4 |
| 610 | 12.0 | 0.25 | 180 | 24.02 | 0.47 | 0.01 | 7.09 | 130 (287) | 1.49 (3.28) | MLH-610 | MLH-610/4 |