

NON RELEASABLE CABLE TIES



Application

For Indoor wire/cable bunching, packing bags etc

Key Industries

Automobile • Chemicals and Refineries • Drug & Pharma
Electrical/Eletronics • Locomotive • Networking • Oil, Gas & Offshore • Packaging Industries • Retail Chain Stores • Ship & Marines • Solar • Telecom • White Goods & Appliances
• Windmill



Specification

Material: Nylon 66
Color: Natural, Black
Operating Temp: -40°C to +85°C
Flammability Rating: UL 94V-2
Installation: By hand or tool cat no. TT-3, TT-4, TT-5
Test Certificate: UL & CE recognized/ROHS compliance
Packing: 100 pcs bag in all sizes & 1000 pcs. bag upto 200mm length
Unit: 100 Pcs/Pkt & 1000 Pcs/K

Features

- Cable tie is an economical & versatile method of cable/wire bunching systems
- Cable tie has self-locking & one-piece construction which ensure the fast & easy installation
- Non releasable cable tie, once locked cannot be opened or reused

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs(lbs)	Maxi. Bundle Dia (mm)	Natural 100 pcs pack Cat No.	Natural 1000 pcs pack Cat No.	Black 100 pcs pack Cat No.	Black 1000 pcs pack Cat No.
75	2.5	1.10	3.0	8 (18)	12	SL-75	SL-75K	SL-75B	SL-75KB
104	2.5	1.10	4.1	8 (18)	22	SL-100	SL-100K	SL-100/B	SL-100K/B
104	2.5	1.10	4.1	12 (27)	22	SL-100X	SL-100XK	SL-100X/B	SL-100XK/B
120	2.5	1.10	4.7	8 (18)	27	SL-120	SL-120K	SL-120/B	SL-120K/B
150	2.5	1.10	5.9	8 (18)	35	SL-150	SL-150K	SL-150/B	SL-150K/B
200	2.5	1.10	7.9	8 (18)	53	SL-200	SL-200K	SL-200/B	SL-200K/B
153	3.6	1.45	6.0	18 (40)	35	SL-150I	SL-150IK	SL-150I/B	SL-150IK/B
153	3.6	1.45	6.0	22 (49)	35	SL-150IX	SL-150IXK	SL-150IX/B	SL-150IXK/B
204	3.6	1.45	8.0	18 (40)	53	SL-200I	SL-200IK	SL-200I/B	SL-200IK/B
250	3.6	1.45	9.8	18 (40)	68	SL-250I		SL-250I/B	
300	3.6	1.45	11.8	18 (40)	80	SL-300I		SL-300I/B	
368	3.6	1.45	14.5	18 (40)	104	SL-368I		SL-368I/B	
200	4.8	1.50	8.0	30 (67)	53	SL-200SX	SL-200SXK	SL-200SX/B	SL-200SXK/B
204	4.8	1.50	8.0	22 (49)	53	SL-200S	SL-200SK	SL-200S/B	SL-200SK/B
254	4.8	1.50	10.0	22 (49)	68	SL-250S		SL-250S/B	
315	4.8	1.50	12.4	22 (49)	86	SL-300S		SL-300S/B	
373	4.8	1.50	14.7	22 (49)	104	SL-368S		SL-368S/B	
455	4.8	1.50	17.9	22 (49)	130	SL-450S		SL-450S/B	
550	4.8	1.50	21.7	22 (49)	165	SL-550S		SL-550S/B	
206	7.8	1.80	8.1	54 (119)	53	SL-200H		SL-200H/B	
256	7.8	1.80	10.1	54 (119)	68	SL-250H		SL-250H/B	
312	7.8	1.80	12.3	54 (119)	82	SL-300H		SL-300H/B	
382	7.8	1.80	15.0	54 (119)	105	SL-380H		SL-380H/B	
453	8.1	1.95	17.8	54 (119)	130	SL-450H		SL-450H/B	
551	9.1	2.00	21.7	81 (180)	163	SL-550H		SL-550H/B	
616	9.1	2.00	24.3	81 (180)	180	SL-610H		SL-610H/B	
716	9.1	2.00	28.2	81 (180)	210	SL-710H		SL-710H/B	
816	9.1	2.00	32.1	81 (180)	240	SL-810H		SL-810H/B	
916	9.1	2.00	36.1	81 (180)	276	SL-910H		SL-910H/B	
1016	9.1	2.00	40.0	81 (180)	305	SL-1010H		SL-1010H/B	

Tolerance Dimension (mm): Length - ±1 to 5, Width - ±0.3 to 0.4, Thickness - ±0.2 to 0.4