

NON RELEASABLE VALUE SERIES CABLE TIES



Application

- For indoor wire/cable bunching, packing bags, etc.



Key Industries

- Chemicals & Refineries • Drug & Pharma
- Electrical / Electronics • Networking • Packaging Industries
 - Retail Chain Stores • Solar • Telecom
 - White Goods & Appliances • Windmill

Specification

Material:	Nylon 66
Color:	Natural, Black
Operating Temp:	-40°C to +85°C
Flammability Rating:	UL 94V-2
Installation:	By hand or tool cat no.....
Test Certificate:	ROHS Compliance
Packing:	100 pcs bag in all sizes & 1000 pcs. bag upto 200mm length
Unit:	100 Pcs/Pkt & 1000 Pcs/K

Features

- Low cost
- Economical design
- Uncompromised tensile strength

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs (lbs)	Maxi. Bundle Dia (mm)	Natural 100 pcs pack Cat No.	Natural 1000 pcs pack Cat No.	Black 100 pcs pack Cat No.	Black 1000 pcs pack Cat No.
100	2.2	0.95	3.9	8 (18)	22	SLV-150I	SLV-100K	SLV-100B	SLV-100KB
150	3.2	1.10	5.9	18 (40)	35	SLV-200I	SLV-150IK	SLV-150I/B	SLV-150IK/B
200	3.2	1.15	7.9	18 (40)	50	SLV-200S	SLV-200IK	SLV-200I/B	SLV-200IK/B
200	4.2	1.30	7.9	22 (49)	50	SLV-250S	SLV-200SK	SLV-200S/B	SLV-200SK/B
250	4.2	1.30	9.8	22 (49)	65	SLV-300S		SLV-250S/B	
300	4.2	1.30	11.8	22 (49)	82	SLV-355S		SLV-300S/B	
355	4.2	1.40	14.0	22 (49)	100	SLV-200H		SLV-355S/B	
200	7.0	1.60	7.9	54 (119)	50	SLV-250H		SLV-200H/B	
250	7.0	1.60	9.8	54 (119)	65	SLV-300H		SLV-250H/B	
300	7.0	1.60	11.8	54 (119)	82	SLV-350H		SLV-300H/B	
350	7.0	1.60	13.8	54 (119)	100	SLV-380H		SLV-350H/B	
380	7.0	1.60	15.0	54 (119)	108	SLV-400H		SLV-380H/B	
400	7.0	1.60	15.7	54 (119)	110	SLV-450H		SLV-400H/B	
450	7.0	1.60	17.7	54 (119)	130	SLV-500H		SLV-450H/B	
500	7.0	1.60	19.7	54 (119)	148	SLV-600H		SLV-500H/B	
600	7.0	1.60	23.6	54 (119)	180			SLV-600H/B	

Tolerance Dimension (mm): Length - ±1 to 3, Width - ±0.1 to 0.2, Thickness - ±0.05 to 0.1