

NON RELEASABLE VALUE SERIES CABLE TIES UV BLACK



Application

- For cable bunching in outdoor weather resistant application



Key Industries

Solar • Telecom • Windmill

Specification

Material:	Nylon 66
Color:	Black
Operating Temp:	-40°F to +85°C
Flammability Rating:	UL 94V-2
Installation:	By hand or tool cat no. TT-3, TT-4, TT-5
Test Certificate:	ROHS compliance
Packing:	100 pcs bag in all sizes & 1000 pcs. bag upto 200mm length
Unit:	100 Pcs/Pkt & 1000 Pcs/K

Features

- Low cost, economical design & uncompromised tensile strength
- UV ties are produced from special grade of UV resistant Nylon 6.6 which gives longer years of life span in outdoor climatic condition

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs (lbs)	Maxi. Bundle Dia (mm)	Cat No. 100 pcs pack (PKT)	Cat No. 1000 pcs pack (K)
100	2.2	0.95	3.9	8 (18)	22	SLV-100U	SLV-100K
150	3.2	1.10	5.9	18 (40)	35	SLV-150/U	SLV-150IKU
200	3.2	1.15	7.9	18 (40)	50	SLV-200/U	SLV-200IKU
200	4.2	1.30	7.9	22 (49)	50	SLV-200S/U	SLV-200SKU
250	4.2	1.30	9.8	22 (49)	65	SLV-250S/U	
300	4.2	1.30	11.8	22 (49)	82	SLV-300S/U	
355	4.2	1.40	14.0	22 (49)	100	SLV-355S/U	
200	7.0	1.60	7.9	54 (119)	50	SLV-200H/U	
250	7.0	1.60	9.8	54 (119)	65	SLV-250H/U	
300	7.0	1.60	11.8	54 (119)	82	SLV-300H/U	
350	7.0	1.60	13.8	54 (119)	100	SLV-350H/U	
380	7.0	1.60	15.0	54 (119)	108	SLV-380H/U	
400	7.0	1.60	15.7	54 (119)	110	SLV-400H/U	
450	7.0	1.60	17.7	54 (119)	130	SLV-450H/U	
500	7.0	1.60	19.7	54 (119)	148	SLV-500H/U	
600	7.0	1.60	23.6	54 (119)	180	SLV-600H/U	

Tolerance Dimension (mm): Length - ± 1 to 3, Width - ± 0.1 to 0.2, Thickness - ± 0.05 to 0.1