

NYLON SCREW MOUNTING SUPPORT

Application

- For supporting & holding cable/wire bunch



Key Industries

- Electrical / Electronics • Locomotive
• Solar • White Goods & Appliances

Specification

| | |
|------------------------|--------------------|
| Material | Nylon-6: UL 94 V-2 |
| Colour : | Natural |
| Operating Temp: | -40°C to +85°C |
| Packing: | 100 Pcs. bag |
| Unit: | 100 Pcs/Pkt |

Features

- Its unique design provides maximum stability to the wire bundles
- Hold wire/cables bundles and help to routing of the same as desired

How to use

- To apply simply fix mount with a screw and secure wire bundles with nylon cable ties

| Size (mm) | A Length (mm) | B Width (mm) | C Height (mm) | L x H Slot (mm) | Ø Mounting Hole (mm) | For Cable Tie Width (mm) | Cat No. |
|-----------|---------------|--------------|---------------|-----------------|----------------------|--------------------------|---------|
| 3.6 | 15.5 | 10.2 | 7 | 6 x 1.2 | 4.5 | 3.6 | NS-3 |
| 4.8 | 16.5 | 11.5 | 7.2 | 7.5 x 1.5 | 4.5 | 4.8 | NS-4 |
| 9 | 22 | 17.5 | 10 | 10 x 2.1 | 4.5 | 7.6/9.2 | NS-9 |
| 12.5 | 41.2 | 18.4 | 15.8 | 13.4 x 3 | 5.7 | 12.5 | NS-12 |
| 19x19 | 19 | 19 | 4.8 | 4.5 x 1.3 | 3.8 | 3.6 | NS-19 |
| 26x26 | 25.5 | 25.5 | 6.8 | 5.5 x 1.4 | 4 | 4.8 | NS-26 |

Tolerance Dimension (mm):- Length - ± 0.5 to 1, Width - ± 0.5 , Height - ± 0.5 , Slot - ± 0.2 to 1, Mounting Hole - ± 0.1 to 0.6