

OUTSIDE SERRATION TIES

Application

- For indoor / outdoor wire cable bunching
- Outside serration ties minimize the damage to the surface of the strapped object or cable insulation



Key Industries

- Automobile • Aviation • Electricals / Electronics
• White Goods & Appliances

Specification

| | |
|-----------------------------|--------------------------|
| Material: | Nylon 66 |
| Color: | Black |
| Operating Temp: | -40°C to +85°C |
| Flammability Rating: | UL 94V-2 |
| Installation: | By hand |
| Test Certificate: | |
| Packing: | 100 pcs bag in all sizes |
| Unit: | 100 Pcs/Pkt |

Features

- Cable tie is an economical & versatile method of cable/wire bunching systems
- Cable tie has self-locking & one-piece construction which ensure the fast & easy installation
- Non-releasable cable tie, once locked cannot be opened or reused

| Length (mm) | Width (mm) | Thickness (mm) | Length (inch) | Tensile Strength Kgs(lbs) | Max. Bundle Ø (mm) | Suitable for Hole Ø (mm) | Chassis Thickness | Cat No. |
|-------------|------------|----------------|---------------|---------------------------|--------------------|--------------------------|-------------------|-----------|
| 150 | 4.7 | 1.35 | 5.9 | 22 (49) | 40 | NA | NA | ATOS-150S |
| 200 | 4.7 | 1.35 | 7.87 | 22 (49) | 55 | NA | NA | ATOS-200S |

Tolerance Dimension (mm): Length - ±1 to 3, Width - ±0.2, Thickness - ±0.2