

# PUSH MOUNT FIR TREE TIES



## Application

- For fixing cable harness in automotive industries
- Also used in aviation, white goods manufacturing & panel building



## Key Industries

- Automobile • Aviation • Electricals / Electronics
- White Goods & Appliances

## Specification

Material:	Nylon 66
Color:	Black
Operating Temp:	-40°C to +85°C
Flammability Rating:	UL 94V-2
Installation:	By hand
Test Certificate:	
Packing:	100 pcs bag in all sizes
Unit:	100 Pcs/Pkt

## Features

- FIR tree tie with disc secures wire harness firmly & minimize access of dust and water
- It is suitable to a varied thickness of chassis or one side thread hole

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs(lbs)	Max. Bundle Ø (mm)	FIR Ø (mm)	Suitable for Hole Ø (mm)	Panel Thickness (mm)	Disc Ø (mm)	Cat No.
161	4.7	1.35	6.33	22 (49)	38	7.5	6.3 - 7.0	0.7 - 3.0	16	ATPF-1617
162	4.7	1.35	6.37	22 (49)	38	7.5	6.3 - 7.0	0.7 - 7.0	16	ATPF-1628
165	4.7	1.35	6.49	22 (49)	38	9.1	8.0 - 8.5	0.6 - 6.0	16	ATPF-1657

**Tolerance Dimension (mm):** Length -  $\pm 1$  to 3, Width -  $\pm 0.2$ , Thickness -  $\pm 0.2$ , FIR Dia -  $\pm 2$ , Suitable for Hole Dia -  $\pm 0.1$  to 0.5