

RELEASABLE CABLE TIES

LIGHT DUTY



Application

- These are useful in wire harnessing where changes are anticipated during development, production or in the field
- Also used for temporary bag packing



Key Industries

- Automobile • Chemicals & Refineries • Drug & Pharma
• Electrical / Electronics • White Goods & Appliances

Specification

Material:	Nylon 66
Color:	Natural, Black
Operating Temp:	-40°C to +85°C
Flammability Rating:	UL 94V-2
Installation:	By hand or tool cat no. TT-3, TT-4, TT-5
Test Certificate:	CE recognized/ROHS compliance
Packing:	100 pcs bag in all sizes & 1000 pcs. bag upto 200mm length
Unit:	100 Pcs/Pkt & 1000 Pcs/K

Features

- The releasable cable tie permits easy release & reuse with tab

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs(lbs)	Maxi. Bundle Dia (mm)	Natural 100 pcs pack Cat No.	Natural 1000 pcs pack Cat No.	Black 100 pcs pack Cat No.	Black 1000 pcs pack Cat No.
153	3.6	1.25	6.0	18 (40)	35	SLR-150	SLR-150K	SLR-150/B	SLR-150K/B
204	4.8	1.50	8.0	22 (49)	53	SLR-200	SLR-200K	SLR-200/B	SLR-200K/B
254	4.8	1.45	10.0	22 (49)	68	SLR-250		SLR-250/B	
315	4.8	1.55	12.4	22 (49)	86	SLR-300		SLR-300/B	
373	4.8	1.55	14.7	22 (49)	104	SLR-368		SLR-368/B	

Tolerance Dimension (mm): Length - ± 1 to 3, Width - ± 0.1 , Thickness - ± 0.1