

# REUSABLE ECONOMY STEEL TIE UNCOATED



## Application

- Suitable for corrosive climate condition, higher temperature and higher tensile strength requirement



## Key Industries

- Aerospace • Chemicals & Refineries • Dairy & Food Processing • Oil, Gas & Offshore • Ship & Marines • Solar • Telecom • Utility • Windmill

## Specification

<b>Material:</b>	Stainless Steel SS 316, SS 3044
<b>Operating Temp:</b>	Uncoated:-80°C to +538°C
<b>Installation:</b>	By hand tie tool (STT 4) and HOOK (STT3)
<b>Test Certificate:</b>	
<b>Packing:</b>	100 pcs bag
<b>Unit:</b>	100 Pcs/Pkt

## Features

- Designed for low cost & low tensile applications
- Smooth edges of ties provide utmost safety while installation

Dimension In MM				Dimension In Inch				Loop Tensile Strength (kgs)/(lbs)	G.W. /100 pcs (Kgs)/(Lbs)	Cat. No. SS 316	Cat No. SS 304
Length	Width	Thickness	Max. Bundle Dia	Length	Width	Thickness	Max. Bundle Dia				
150	5.0	0.50	30	5.91	0.20	0.02	1.18	120 (264)	0.38 (0.85)	RTE-150	RTE-150/4
230	5.0	0.50	54	9.06	0.20	0.02	2.13	120 (264)	0.55 (1.21)	RTE-230	RTE-230/4
330	5.0	0.50	85	12.99	0.20	0.02	3.35	120 (264)	0.75 (1.65)	RTE-330	RTE-330/4
450	5.0	0.50	125	17.72	0.20	0.02	4.92	120 (264)	0.99 (2.18)	RTE-450	RTE-450/4
610	5.0	0.50	175	24.02	0.20	0.02	6.89	120 (264)	1.31 (2.88)	RTE-610	RTE-610/4
762	5.0	0.50	220	30.00	0.20	0.02	8.66	120 (264)	1.61 (3.551)	RTE-762	RTE-762/4
914	5.0	0.50	270	35.98	0.20	0.02	10.63	120 (264)	1.91 (4.220)	RTE-914	RTE-914/4