

# SELF ADHESIVE FLAT CABLE CLAMP

## Application

- For supporting & holding flat cable

## Key Industries

- Automobile
- Electrical / Electronics
- Locomotive
- White Goods & Appliances
- Windmill



## Specification

<b>Material</b>	Nylon-6: UL 94 V-2 (Backed with Adhesive tape)
<b>Colour :</b>	Natural Clip Support
<b>Operating Temp:</b>	-29°C to +49°C (Max. Intermittent Temp. i.e. less than 2 hrs. 70°C)
<b>Packing:</b>	100 Pcs. bag
<b>Unit:</b>	100 Pcs/Pkt

## Features

- Low profile & flexible top allows easy removal & replacement of desired cables
- Rubber based closed cell foam adhesive is used for better surface adhesion
- Holds single or multiple layers of flat ribbon cable neatly & firmly

## How to use

- To apply, simply peel off backing paper and apply mount to any clean smooth, grease-free surface
- Place flat ribbon cable in nylon clamp

Description	Adhesive Tape	L Length (mm)	B width (mm)	C Height (mm)	Mounting Hole (mm)	Cat No.
Clip Support	3M Green	25.0	24.5	5.5	3.5	TMF-25G
Clip Support	Four Pillar	25.0	24.5	5.5	3.5	TMF-25
Small Flat Support	Four Pillar	28.5	14.0	7.5	-	TMF-28
Big Flat Support	Four Pillar	28.5	24.5	7.5	-	TMF-28B
Big Clip Support	Four Pillar	46.0	19.5	13.0	-	TMF-50

Tolerance Dimension (mm):- Length -  $\pm 0.5$  to 1, Width -  $\pm 0.5$  to 1, Height -  $\pm 0.5$  to 3, Mounting Hole -  $\pm 0.1$  to 0.6