SELF ADHESIVE ROUND ADJUSTABLE CABLE CLAMP



Application

 For supporting & holding cable/wire bunch of different diameter



Key Industires

Automobile • Electrical / Electronics • Locomotive

White Goods & Appliances
 Windmill

Specification

Material Nylon-6: UL 94 V-2 (Backed with Adhesive tape)

Colour: Natural

Operating Temp: -29°C to +49°C (Max. Intermittent Temp. i.e. less than 2 hrs. 70°C)

Packing: 100 Pcs. bag
Unit: 100 Pcs/Pkt

Features

- Multistage, locking design can accommodate different cable size in one clamp
- Rubber based closed cell foam adhesive is used for better surface adhesion.
- Used where cable/wire bundling changes are anticipated or temporary bundling is required

How to use

- To apply, simply peel off backing paper and apply mount to any clean smooth, arease-free surface
- Place flat ribbon cable in nylon clamp

Description	Adhesive Tape	A Length (mm)	B Width (mm)	C Height (rnm)	Adh. Tape	Cat No.
Ladder Support	Four Pillar	28.90	20.10	30.95	Yellow	TMRA-L
Crick Support	Four Pillar	28.80	23.70	23.95	Yellow	TMRA-C
Tolerance Dimension (mm):- Length - ± 0.5 to 1, Width - ± 0.5 to 1, Height - ± 0.5 to 3						