

SPIRAL WRAPPING TUBE HD



Application

- Abrasion protection of wire & cable insulation & hydraulic or pneumatic tubing

Key Industries

- Automobile • Electrical / Electronics
● White Goods & Appliances • Windmill



Specification

Material	P.E.
Colour :	Natural, Black
Operating Temp:	-40°C to +85°C
Test Certificated:	ROHS Compliance
Packing:	50 Mtrs., 25 Mtrs., 10 Mtrs. Roll

Features

- Can reuse when the change are required in bundle
- Can use in gapped manner where flexibility, breakouts & economy is required
- Can use in butted manner where rigidity & protection is required against continuously abrasion

Size	I D (mm)	OD (mm)	Pitch (mm)	Thickness (mm)	Bundle Range (mm)	Std Qty/Roll	Cat No. Natural	Cat No. Black
1/8"	2.1	3.2	3.2	0.55	1.6 - 12.7	50 Mtrs.	ST-3	ST-3B
3/8"	7.8	9.5	9.5	0.85	8.0 - 76	25 Mtrs.	ST-9	ST-9B
1/2"	10.5	12.7	12.7	1.1	19.1 - 102	25 Mtrs.	ST-12	ST-12B
5/8"	13.6	16.0	16.0	1.2	22 - 114	25 Mtrs.	ST-15	ST-15B
3/4"	16.4	19.0	19.0	1.3	25 - 127	25 Mtrs.	ST-19	ST-19B
1"	22.8	25.4	25.4	1.3	25 - 127	25 Mtrs.	ST-25	ST-25B
1 1/4"	4.8	6.3	6.3	0.75	4.8 - 40	50 Mtrs.	ST-6	ST-6B
1 1/2"	34.0	38.1	38.1	2.0	43 - 170	10 Mtrs.	ST-38	ST-38B

Tolerance Dimension (mm):- I D - ±0.5 to 2, O D - ±0.5 to 2, Pitch - ±0.5 to 2, Thickness - ±0.1 to 0.2