

# SS BAND BALL LOCK COATED STRIP

## Application

- The application which require various bundle diameters, is not possible to tie with standard range of ball lock ties which can be bundled with ball lock band & head



## Specification

**Material:** SS 316  
**Packing:** 50 Mtrs (1 65 Ft.)/Roll in box

Width		Thickness		SS Grade	Tensile Strength		Used with Ball Lock Head	Package Qty. per Roll	G. wt. / Std. Pkg.		Cat. No.	Catalogue
inchs	mm	inches	mm		Kgs.	Lbs.			Kgs.	Lbs.		OK/Changed
0.18	4.6	0.03	0.75	SS 316	60	132	SBBLH-46	50 Mtrs (165 Ft.)	0.84	1.85	SBBL-4CT	New Addition
0.18	4.6	0.03	0.75	SS 304	60	132	SBBLH-46	50 Mtrs (165 Ft.)	0.84	1.85	SBBL-4CT/4	New Addition
0.18	4.6	0.03	0.75	SS 201	60	132	SBBLH-46	50 Mtrs (165 Ft.)	0.84	1.85	SBBL-4CT/1	New Addition
0.31	7.9	0.03	0.75	SS 316	170	375	SBBLH-79	50 Mtrs (165 Ft.)	1.37	3.00	SBBL-7CT	New Addition
0.31	7.9	0.03	0.75	SS 304	170	375	SBBLH-79	50 Mtrs (165 Ft.)	1.37	3.00	SBBL-7CT/4	New Addition
0.31	7.9	0.03	0.75	SS 201	170	375	SBBLH-79	50 Mtrs (165 Ft.)	1.37	3.00	SBBL-7CT/1	New Addition
0.50	12.7	0.03	0.75	SS 316	267	589	SBBLH-127	50 Mtrs (165 Ft.)	2.13	4.68	SBBL-12CT	New Addition
0.50	12.7	0.03	0.75	SS 304	267	589	SBBLH-127	50 Mtrs (165 Ft.)	2.13	4.68	SBBL-12CT/4	New Addition
0.50	12.7	0.03	0.75	SS 201	267	589	SBBLH-127	50 Mtrs (165 Ft.)	2.13	4.68	SBBL-12CT/1	New Addition
0.63	15.9	0.03	0.75	SS 316	400	882	SBBLH-159	50 Mtrs (165 Ft.)	3.47	7.63	SBBL-15CT	New Addition
0.63	15.9	0.03	0.75	SS 304	400	882	SBBLH-159	50 Mtrs (165 Ft.)	3.47	7.63	SBBL-15CT/4	New Addition
0.63	15.9	0.03	0.75	SS 201	400	882	SBBLH-159	50 Mtrs (165 Ft.)	3.47	7.63	SBBL-15CT/1	New Addition