

# SS BAND BALL LOCK UNCOATED STRIP



## Application

- The application which require various bundle diameters, is not possible to tie with standard range of ball lock ties which can be bundled with ball lock band & head



## Specification

**Material:** SS 316  
**Packing:** 61 Mtrs (200 Ft.)/Roll in box

Width		Thickness		SS Grade	Tensile Strength		Used with Ball Lock Head	Package Qty. per Roll	G.wt. / Std. Pkg.		Cat. No.
Inchs	mm	inches	mm		Kgs.	Lbs.			Kgs.	Lbs.	
0.18	4.6	0.01	0.25	SS 316	60	132	SBBLH-46	61 Mtrs (200 Ft.)	0.65	1.43	SBBL-4
0.18	4.6	0.01	0.25	SS 304	60	132	SBBLH-46	61 Mtrs (200 Ft.)	0.65	1.43	SBBL-4/4
0.18	4.6	0.01	0.25	SS 201	60	132	SBBLH-46	61 Mtrs (200 Ft.)	0.65	1.43	SBBL-4/1
0.31	7.9	0.01	0.25	SS 316	170	375	SBBLH-79	61 Mtrs (200 Ft.)	1.06	2.33	SBBL-7
0.31	7.9	0.01	0.25	SS 304	170	375	SBBLH-79	61 Mtrs (200 Ft.)	1.06	2.33	SBBL-7/4
0.31	7.9	0.01	0.25	SS 201	170	375	SBBLH-79	61 Mtrs (200 Ft.)	1.06	2.33	SBBL-7/1
0.50	12.7	0.01	0.25	SS 316	267	589	SBBLH-127	61 Mtrs (200 Ft.)	1.65	3.63	SBBL-12
0.50	12.7	0.01	0.25	SS 304	267	589	SBBLH-127	61 Mtrs (200 Ft.)	1.65	3.63	SBBL-12/4
0.50	12.7	0.01	0.25	SS 201	267	589	SBBLH-127	61 Mtrs (200 Ft.)	1.65	3.63	SBBL-12/1
0.63	15.9	0.01	0.25	SS 316	400	882	SBBLH-159	61 Mtrs (200 Ft.)	3.04	6.70	SBBL-15
0.63	15.9	0.01	0.25	SS 304	400	882	SBBLH-159	61 Mtrs (200 Ft.)	3.04	6.70	SBBL-15/4
0.63	15.9	0.01	0.25	SS 201	400	882	SBBLH-159	61 Mtrs (200 Ft.)	3.04	6.70	SBBL-15/1