

SS BAND EHD UNCOATED



Application

- Cable bundling application for higher tensile load and high vibration
- For various size of cable diameter requirement



Key Industries

- Aerospace ● Chemicals & Refineries ● Dairy & Food Processing ● Oil, Gas & Offshore ● Ship & Marines ● Signage & Signals ● Solar ● Telecom ● Utility ● Windmill

Specification

- Material:** SS 201
Installation: By tool cat no. TB-1
Test Certificate:
Packing: 30.5 Mtrs (100 Ft.)/Roll in box

Features

- Provides higher tensile strength
- Ideal for use in high vibration application
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of band provide utmost safety while installation

Width		Thickness		SS Grade	Tensile Strength		Used with Buckle	Package Qty. per Roll	G.wt. / Std. Pkg.		Cat. No.
inchs	mm	inches	mm		Kgs.	Lbs.			Kgs.	Lbs.	
3/4	19.0	0.044	1.12	SS 316	1495	3296	SBB-19	30.5 Mtrs (100 Ft.)	5.3	11.6	SBEH-19
3/4	19.0	0.044	1.12	SS 304	1495	3296	SBB-19	30.5 Mtrs (100 Ft.)	5.3	11.6	SBEH-19/4
3/4	19.0	0.044	1.12	SS 201	1495	3296	SBB-19	30.5 Mtrs (100 Ft.)	5.3	11.6	SBEH-19/1
1	25.4	0.044	1.12	SS 316	1993	4394	SBB-25	30.5 Mtrs (100 Ft.)	6.2	13.7	SBEH-25
1	25.4	0.044	1.12	SS 304	1993	4394	SBB-25	30.5 Mtrs (100 Ft.)	6.2	13.7	SBEH-25/4
1	25.4	0.044	1.12	SS 201	1993	4394	SBB-25	30.5 Mtrs (100 Ft.)	6.2	13.7	SBEH-25/1
1 1/4	31.8	0.044	1.12	SS 316	2492	5494	SBB-32	30.5 Mtrs (100 Ft.)	7.8	17.2	SBEH-32
1 1/4	31.8	0.044	1.12	SS 304	2492	5494	SBB-32	30.5 Mtrs (100 Ft.)	7.8	17.2	SBEH-32/4
1 1/4	31.8	0.044	1.12	SS 201	2492	5494	SBB-32	30.5 Mtrs (100 Ft.)	7.8	17.2	SBEH-32/1