

SS BAND FIXED LENGTH UNCOATED



Application

- Clamps hose, poles, pipes, cables etc.



Key Industries

- Aerospace • Chemicals & Refineries • Dairy & Food Processing • Oil, Gas & Offshore • Ship & Marines • Signage & Signals • Solar • Telecom • Utility • Windmill

Specification

Material: SS 316
Installation:
Test Certificate:
Packing: 50 Pcs. box

Features

- Provides higher tensile strength
- Ideal for use in high vibration application
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of band provide utmost safety while installation

Length		Width		Thickness		SS Grade	Maximum Bundle Dia		Tensile Strength		Package Qty. per Box	G.W/ Std. Pkg. (100 Pcs.) for Coated Bands Fixed Length	
inchs	mm	inchs	mm	inches	mm		inchs	mm	Kbs.	Lbs.		Kgs.	Lbs.
10	254	1/4	6.3	0.015	0.38	SS 316	2	50	140	309	50 Pcs.	0.36	0.79
10	254	1/4	6.3	0.015	0.38	SS 304	2	50	140	309	50 Pcs.	0.36	0.79
10	254	1/4	6.3	0.015	0.38	SS 201	2	50	140	309	50 Pcs.	0.36	0.79
12	305	1/4	6.3	0.015	0.38	SS 316	2.55	65	140	309	50 Pcs.	0.41	0.90
12	305	1/4	6.3	0.015	0.38	SS 304	2.55	65	140	309	50 Pcs.	0.41	0.90
12	305	1/4	6.3	0.015	0.38	SS 201	2.55	65	140	309	50 Pcs.	0.41	0.90
153/4	400	1/4	6.3	0.015	0.38	SS 316	3.5	89	140	309	50 Pcs.	0.51	1.12
153/4	400	1/4	6.3	0.015	0.38	SS 304	3.5	89	140	309	50 Pcs.	0.51	1.12
153/4	400	1/4	6.3	0.015	0.38	SS 201	3.5	89	140	309	50 Pcs.	0.51	1.12
191/2	495	1/4	6.3	0.015	0.38	SS 316	5.3	135	140	309	50 Pcs.	0.62	1.36
191/2	495	1/4	6.3	0.015	0.38	SS 304	5.3	135	140	309	50 Pcs.	0.62	1.36
191/2	495	1/4	6.3	0.015	0.38	SS 201	5.3	135	140	309	50 Pcs.	0.62	1.36
251/2	648	1/4	6.3	0.015	0.38	SS 316	6.5	165	140	309	50 Pcs.	0.78	1.71
251/2	648	1/4	6.3	0.015	0.38	SS 304	6.5	165	140	309	50 Pcs.	0.78	1.71
251/2	648	1/4	6.3	0.015	0.38	SS 201	6.5	165	140	309	50 Pcs.	0.78	1.71
331/2	851	1/4	6.3	0.015	0.38	SS 316	8.6	218	140	309	50 Pcs.	0.99	2.18
331/2	851	1/4	6.3	0.015	0.38	SS 304	8.6	218	140	309	50 Pcs.	0.99	2.18
331/2	851	1/4	6.3	0.015	0.38	SS 201	8.6	218	140	309	50 Pcs.	0.99	2.18
41	1041	1/4	6.3	0.015	0.38	SS 316	11.8	300	140	309	50 Pcs.	1.20	2.64
41	1041	1/4	6.3	0.015	0.38	SS 304	11.8	300	140	309	50 Pcs.	1.20	2.64
41	1041	1/4	6.3	0.015	0.38	SS 201	11.8	300	140	309	50 Pcs.	1.20	2.64

SS BAND FIXED LENGTH UNCOATED



Length		Width		Thickness		SS Grade	Maximum Bundle Dia		Tensile Strength		Package Qty.	G.W/ Std. Pkg. (100 Pcs.) for Coated Bands Fixed Length	
inches	mm	inches	mm	inches	mm		inches	mm	Kbs.	Lbs.		Kbs.	Lbs.
12	305	3/8	9.5	0.015	0.38	SS 316	2.55	65	204	450	50 Pcs.	0.69	1.52
12	305	3/8	9.5	0.015	0.38	SS 304	2.55	65	204	450	50 Pcs.	0.69	1.52
12	305	3/8	9.5	0.015	0.38	SS 201	2.55	65	204	450	50 Pcs.	0.69	1.52
153/4	400	3/8	9.5	0.015	0.38	SS 316	3.5	89	204	450	50 Pcs.	0.85	1.87
153/4	400	3/8	9.5	0.015	0.38	SS 304	3.5	89	204	450	50 Pcs.	0.85	1.87
153/4	400	3/8	9.5	0.015	0.38	SS 201	3.5	89	204	450	50 Pcs.	0.85	1.87
191/2	495	3/8	9.5	0.015	0.38	SS 316	5.3	135	204	450	50 Pcs.	1.01	2.22
191/2	495	3/8	9.5	0.015	0.38	SS 304	5.3	135	204	450	50 Pcs.	1.01	2.22
191/2	495	3/8	9.5	0.015	0.38	SS 201	5.3	135	204	450	50 Pcs.	1.01	2.22
251/2	648	3/8	9.5	0.015	0.38	SS 316	6.5	165	204	450	50 Pcs.	1.25	2.75
251/2	648	3/8	9.5	0.015	0.38	SS 304	6.5	165	204	450	50 Pcs.	1.25	2.75
251/2	648	3/8	9.5	0.015	0.38	SS 201	6.5	165	204	450	50 Pcs.	1.25	2.75
331/2	851	3/8	9.5	0.015	0.38	SS 316	8.6	218	204	450	50 Pcs.	1.57	3.46
331/2	851	3/8	9.5	0.015	0.38	SS 304	8.6	218	204	450	50 Pcs.	1.57	3.46
331/2	851	3/8	9.5	0.015	0.38	SS 201	8.6	218	204	450	50 Pcs.	1.57	3.46
41	1041	3/8	9.5	0.015	0.38	SS 316	11.8	300	204	450	50 Pcs.	1.89	4.16
41	1041	3/8	9.5	0.015	0.38	SS 304	11.8	300	204	450	50 Pcs.	1.89	4.16
41	1041	3/8	9.5	0.015	0.38	SS 201	11.8	300	204	450	50 Pcs.	1.89	4.16
12	305	1/2	12.7	0.015	0.38	SS 316	2.55	65	311	686	50 Pcs.	1.00	2.20
12	305	1/2	12.7	0.015	0.38	SS 304	2.55	65	311	686	50 Pcs.	1.00	2.20
12	305	1/2	12.7	0.015	0.38	SS 201	2.55	65	311	686	50 Pcs.	1.00	2.20
153/4	400	1/2	12.7	0.015	0.38	SS 316	3.5	89	311	686	50 Pcs.	1.21	2.66
153/4	400	1/2	12.7	0.015	0.38	SS 304	3.5	89	311	686	50 Pcs.	1.21	2.66
153/4	400	1/2	12.7	0.015	0.38	SS 201	3.5	89	311	686	50 Pcs.	1.21	2.66
191/2	495	1/2	12.7	0.015	0.38	SS 316	5.3	135	311	686	50 Pcs.	1.42	3.13
191/2	495	1/2	12.7	0.015	0.38	SS 304	5.3	135	311	686	50 Pcs.	1.42	3.13
191/2	495	1/2	12.7	0.015	0.38	SS 201	5.3	135	311	686	50 Pcs.	1.42	3.13
251/2	648	1/2	12.7	0.015	0.38	SS 316	6.5	165	311	686	50 Pcs.	1.75	3.85
251/2	648	1/2	12.7	0.015	0.38	SS 304	6.5	165	311	686	50 Pcs.	1.75	3.85
251/2	648	1/2	12.7	0.015	0.38	SS 201	6.5	165	311	686	50 Pcs.	1.75	3.85
331/2	851	1/2	12.7	0.015	0.38	SS 316	8.6	218	311	686	50 Pcs.	2.17	4.78
331/2	851	1/2	12.7	0.015	0.38	SS 304	8.6	218	311	686	50 Pcs.	2.17	4.78
331/2	851	1/2	12.7	0.015	0.38	SS 201	8.6	218	311	686	50 Pcs.	2.17	4.78
41	1041	1/2	12.7	0.015	0.38	SS 316	11.8	300	311	686	50 Pcs.	2.60	5.73
41	1041	1/2	12.7	0.015	0.38	SS 304	11.8	300	311	686	50 Pcs.	2.60	5.73
41	1041	1/2	12.7	0.015	0.38	SS 201	11.8	300	311	686	50 Pcs.	2.60	5.73
12	305	5/8	15.9	0.015	0.38	SS 316	2.55	65	340	750	50 Pcs.	1.32	2.91
12	305	5/8	15.9	0.015	0.38	SS 304	2.55	65	340	750	50 Pcs.	1.32	2.91
12	305	5/8	15.9	0.015	0.38	SS 201	2.55	65	340	750	50 Pcs.	1.32	2.91
153/4	400	5/8	15.9	0.015	0.38	SS 316	3.5	89	340	750	50 Pcs.	1.58	3.48
153/4	400	5/8	15.9	0.015	0.38	SS 304	3.5	89	340	750	50 Pcs.	1.58	3.48
153/4	400	5/8	15.9	0.015	0.38	SS 201	3.5	89	340	750	50 Pcs.	1.58	3.48
191/2	495	5/8	15.9	0.015	0.38	SS 316	5.3	135	340	750	50 Pcs.	1.85	4.07
191/2	495	5/8	15.9	0.015	0.38	SS 304	5.3	135	340	750	50 Pcs.	1.85	4.07
191/2	495	5/8	15.9	0.015	0.38	SS 201	5.3	135	340	750	50 Pcs.	1.85	4.07
251/2	648	5/8	15.9	0.015	0.38	SS 316	6.5	165	340	750	50 Pcs.	2.25	4.96
251/2	648	5/8	15.9	0.015	0.38	SS 304	6.5	165	340	750	50 Pcs.	2.25	4.96
251/2	648	5/8	15.9	0.015	0.38	SS 201	6.5	165	340	750	50 Pcs.	2.25	4.96
331/2	851	5/8	15.9	0.015	0.38	SS 316	8.6	218	340	750	50 Pcs.	2.78	6.13
331/2	851	5/8	15.9	0.015	0.38	SS 304	8.6	218	340	750	50 Pcs.	2.78	6.13
331/2	851	5/8	15.9	0.015	0.38	SS 201	8.6	218	340	750	50 Pcs.	2.78	6.13
41	1041	5/8	15.9	0.015	0.38	SS 316	11.8	300	340	750	50 Pcs.	3.32	7.32
41	1041	5/8	15.9	0.015	0.38	SS 304	11.8	300	340	750	50 Pcs.	3.32	7.32
41	1041	5/8	15.9	0.015	0.38	SS 201	11.8	300	340	750	50 Pcs.	3.32	7.32
12	305	3/4	19.0	0.015	0.38	SS 316	2.55	65	408	900	25 Pcs.	1.43	3.15
12	305	3/4	19.0	0.015	0.38	SS 304	2.55	65	408	900	25 Pcs.	1.43	3.15
12	305	3/4	19.0	0.015	0.38	SS 201	2.55	65	408	900	25 Pcs.	1.43	3.15
153/4	400	3/4	19.0	0.015	0.38	SS 316	3.5	89	408	900	25 Pcs.	1.75	3.85
153/4	400	3/4	19.0	0.015	0.38	SS 304	3.5	89	408	900	25 Pcs.	1.75	3.85
153/4	400	3/4	19.0	0.015	0.38	SS 201	3.5	89	408	900	25 Pcs.	1.75	3.85
191/2	495	3/4	19.0	0.015	0.38	SS 316	5.3	135	408	900	25 Pcs.	2.07	4.56
191/2	495	3/4	19.0	0.015	0.38	SS 304	5.3	135	408	900	25 Pcs.	2.07	4.56
191/2	495	3/4	19.0	0.015	0.38	SS 201	5.3	135	408	900	25 Pcs.	2.07	4.56
251/2	648	3/4	19.0	0.015	0.38	SS 316	6.5	165	408	900	25 Pcs.	2.54	5.60
251/2	648	3/4	19.0	0.015	0.38	SS 304	6.5	165	408	900	25 Pcs.	2.54	5.60
251/2	648	3/4	19.0	0.015	0.38	SS 201	6.5	165	408	900	25 Pcs.	2.54	5.60
331/2	851	3/4	19.0	0.015	0.38	SS 316	8.6	218	408	900	25 Pcs.	3.18	7.01
331/2	851	3/4	19.0	0.015	0.38	SS 304	8.6	218	408	900	25 Pcs.	3.18	7.01
331/2	851	3/4	19.0	0.015	0.38	SS 201	8.6	218	408	900	25 Pcs.	3.18	7.01
41	1041	3/4	19.0	0.015	0.38	SS 316	11.8	300	408	900	25 Pcs.	3.82	8.42
41	1041	3/4	19.0	0.015	0.38	SS 304	11.8	300	408	900	25 Pcs.	3.82	8.42
41	1041	3/4	19.0	0.015	0.38	SS 201	11.8	300	408	900	25 Pcs.	3.82	8.42