

SS BAND HD COATED



Application

- Cable bundling application for higher tensile load and high vibration
- For various size of cable diameter requirement



Key Industries

- Aerospace
- Chemicals & Refineries
- Dairy & Food Processing
- Oil, Gas & Offshore
- Ship & Marines
- Signage & Signals
- Solar
- Telecom
- Utility
- Windmill

Specification

- Material:** SS 316, SS 201
- Coating:** Black PPA - Thermoplastic or Polyester
- Installation:** By tool cat no. TB-1
- Test Certificate:**
- Packing:** 25 Mtrs (82.5 Ft.)/Roll in box

Features

- Coated band provides long term life in corrosive climate condition
- Provides higher tensile strength
- Ideal for use in high vibration application
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of band provide utmost safety while installation
- Coating material is non-toxic, halogen free, low smoke and UV resistant

Width		Thickness		SS Grade	Tensile Strength		Used with Buckle/Clip	Package Qty. per Roll	G.wt. / Std. Pkg.		Cat. No.
inchs	mm	inches	mm		Kgs.	Lbs.			Kgs.	Lbs.	
3/16	4.8	0.035	0.88	SS 316	127	280	SBB-4 , SBC-4	25 Mtrs (82.5 Ft.)	0.62	1.36	SBH-4CT
3/16	4.8	0.035	0.88	SS 201	158	348	SBB-4 , SBC-4	25 Mtrs (82.5 Ft.)	0.62	1.36	SBH-4CT/1
3/16	4.8	0.035	0.88	Galvanized	-	-	SBB-4 , SBC-4	25 Mtrs (82.5 Ft.)	0.62	1.36	
1/4	6.3	0.040	1.01	SS 316	180	397	SBB-6 , SBC-6	25 Mtrs (82.5 Ft.)	0.94	2.07	SBH-6CT
1/4	6.3	0.040	1.01	SS 201	226	498	SBB-6 , SBC-6	25 Mtrs (82.5 Ft.)	0.94	2.07	SBH-6CT/1
1/4	6.3	0.040	1.01	Galvanized	-	-	SBB-6 , SBC-6	25 Mtrs (82.5 Ft.)	0.94	2.07	
3/8	9.5	0.044	1.13	SS 316	340	750	SBB-9 , SBC-9	25 Mtrs (82.5 Ft.)	1.59	3.50	SBH-9CT
3/8	9.5	0.044	1.13	SS 201	408	899	SBB-9 , SBC-9	25 Mtrs (82.5 Ft.)	1.59	3.50	SBH-9CT/1
3/8	9.5	0.044	1.13	Galvanized	317	700	SBB-9 , SBC-9	25 Mtrs (82.5 Ft.)	1.59	3.50	
1/2	12.7	0.050	1.26	SS 316	543	1197	SBB-12 , SBC-12	25 Mtrs (82.5 Ft.)	2.41	5.30	SBH-12CT
1/2	12.7	0.050	1.26	SS 201	680	1499	SBB-12 , SBC-12	25 Mtrs (82.5 Ft.)	2.41	5.30	SBH-12CT/1
1/2	12.7	0.050	1.26	Galvanized	510	1125	SBB-12 , SBC-12	25 Mtrs (82.5 Ft.)	2.41	5.30	
5/8	15.9	0.050	1.26	SS 316	680	1499	SBB-15 , SBC-15	25 Mtrs (82.5 Ft.)	3.00	6.60	SBH-15CT
5/8	15.9	0.050	1.26	SS 201	850	1874	SBB-15 , SBC-15	25 Mtrs (82.5 Ft.)	3.00	6.60	SBH-15CT/1
5/8	15.9	0.050	1.26	Galvanized	636	1405	SBB-15 , SBC-15	25 Mtrs (82.5 Ft.)	3.00	6.60	
3/4	19.0	0.050	1.26	SS 316	815	1797	SBB-19 , SBC-19	25 Mtrs (82.5 Ft.)	3.57	7.85	SBH-19CT
3/4	19.0	0.050	1.26	SS 201	1020	2249	SBB-19 , SBC-19	25 Mtrs (82.5 Ft.)	3.57	7.85	SBH-19CT/1
3/4	19.0	0.050	1.26	Galvanized	765	1690	SBB-19 , SBC-19	25 Mtrs (82.5 Ft.)	3.57	7.85	