

SS BAND LD COATED



Application

- Cable bundling application for higher tensile load and high vibration
- For various size of cable diameter requirement



Key Industries

- Aerospace ● Chemicals & Refineries ● Dairy & Food Processing ● Oil, Gas & Offshore ● Ship & Marines ● Signage & Signals ● Solar ● Telecom ● Utility ● Windmill

Specification

- Material:** SS 316
Coating: Black PPA-Thermoplastic or Polyester
Installation: By tool cat. no. TB-1
Test Certificate:
Packing: 25 Mtrs (82.5 Ft.)/Roll in box

Features

- Coated band provides long term life in corrosive climate condition
- Provides higher tensile strength
- Ideal for use in high vibration application
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of ties provide utmost safety while installation
- Coating material is non-toxic, halogen free, low smoke and UV resistant

Width		Thickness		SS Grade	Tensile Strength		Used with Clip	Package Qty. per Roll	G.wt. / Std. Pkg.		Cat. No.
inchs	mm	inches	mm		Kgs.	Lbs.			Kgs.	Lbs.	
1/4	6.3	0.048	1.22	SS 316	152	335	SBC-6	25 Mtrs (82.5 Ft.)	0.9	2.0	SBL-638CT
1/4	6.3	0.048	1.22	SS 304	152	335	SBC-6	25 Mtrs (82.5 Ft.)	0.9	2.0	SBL-638CT/4
1/4	6.3	0.048	1.22	SS 201	152	335	SBC-6	25 Mtrs (82.5 Ft.)	0.9	2.0	SBL-638CT/1
3/8	9.5	0.048	1.22	SS 316	228	503	SBC-9	25 Mtrs (82.5 Ft.)	1.2	2.6	SBL-938CT
3/8	9.5	0.048	1.22	SS 304	228	503	SBC-9	25 Mtrs (82.5 Ft.)	1.2	2.6	SBL-938CT/4
3/8	9.5	0.048	1.22	SS 201	228	503	SBC-9	25 Mtrs (82.5 Ft.)	1.2	2.6	SBL-938CT/1
1/2	12.7	0.048	1.22	SS 316	303	668	SBC-12	25 Mtrs (82.5 Ft.)	1.6	3.5	SBL-1238CT
1/2	12.7	0.048	1.22	SS 304	303	668	SBC-12	25 Mtrs (82.5 Ft.)	1.6	3.5	SBL-1238CT/4
1/2	12.7	0.048	1.22	SS 201	303	668	SBC-12	25 Mtrs (82.5 Ft.)	1.6	3.5	SBL-1238CT/1
5/8	15.9	0.048	1.22	SS 316	380	838	SBC-15	25 Mtrs (82.5 Ft.)	2.0	4.4	SBL-1538CT
5/8	15.9	0.048	1.22	SS 304	380	838	SBC-15	25 Mtrs (82.5 Ft.)	2.0	4.4	SBL-1538CT/4
5/8	15.9	0.048	1.22	SS 201	380	838	SBC-15	25 Mtrs (82.5 Ft.)	2.0	4.4	SBL-1538CT/1
3/4	19.0	0.048	1.22	SS 316	453	999	SBC-19	25 Mtrs (82.5 Ft.)	2.4	5.3	SBL-1938CT
3/4	19.0	0.048	1.22	SS 304	453	999	SBC-19	25 Mtrs (82.5 Ft.)	2.4	5.3	SBL-1938CT/4
3/4	19.0	0.048	1.22	SS 201	453	999	SBC-19	25 Mtrs (82.5 Ft.)	2.4	5.3	SBL-1938CT/1