

SS BAND LD UNCOATED



Application

- Cable bundling application for higher tensile load and high vibration
- For various size of cable diameter requirement



Key Industries

Aerospace • Chemicals & Refineries • Dairy & Food Processing • Oil, Gas & Offshore • Ship & Marines
• Signage & Signals • Solar • Telecom • Utility • Windmill

Specification

Material:	SS 304
Installation:	By tool cat no. TB-1
Test Certificate:	
Packing:	30.5 Mtrs (100 Ft.)/Roll in box

Features

- Provides higher tensile strength
- Ideal for use in high vibration application
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of band provide utmost safety while installation

SS BAND LD UNCOATED



Width		Thickness		SS Grade	Tensile Strength		Used with Buckle/Clip	Package Qty. per Roll	G.wt. / Std. Pkg.		Cat. No.
inches	mm	inches	mm		Kgs.	Lbs.			Kgs.	Lbs.	
1/4	6.3	0.015	0.38	SS 316	140	309	SBB-6, SBC-6	30.5 Mtrs (100 Ft.)	0.80	1.76	SBL-638
1/4	6.3	0.015	0.38	SS 304	140	309	SBB-6, SBC-6	30.5 Mtrs (100 Ft.)	0.80	1.76	SBL-638/4
1/4	6.3	0.015	0.38	SS 201	140	309	SBB-6, SBC-6	30.5 Mtrs (100 Ft.)	0.80	1.76	SBL-638/1
3/8	9.5	0.015	0.38	SS 316	204	450	SBB-9, SBC-9	30.5 Mtrs (100 Ft.)	1.00	2.2	SBL-938
3/8	9.5	0.015	0.38	SS 304	204	450	SBB-9, SBC-9	30.5 Mtrs (100 Ft.)	1.00	2.2	SBL-938/4
3/8	9.5	0.015	0.38	SS 201	204	450	SBB-9, SBC-9	30.5 Mtrs (100 Ft.)	1.00	2.2	SBL-938/1
3/8	9.5	0.020	0.51	SS 316	272	600	SBB-9, SBC-9	30.5 Mtrs (100 Ft.)	1.20	2.8	SBL-951
3/8	9.5	0.020	0.51	SS 304	272	600	SBB-9, SBC-9	30.5 Mtrs (100 Ft.)	1.20	2.8	SBL-951/4
3/8	9.5	0.020	0.51	SS 201	272	600	SBB-9, SBC-9	30.5 Mtrs (100 Ft.)	1.20	2.8	SBL-951/1
1/2	12.7	0.015	0.38	SS 316	272	600	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	1.30	2.9	SBL-1238
1/2	12.7	0.015	0.38	SS 304	272	600	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	1.30	2.9	SBL-1238/4
1/2	12.7	0.015	0.38	SS 201	272	600	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	1.30	2.9	SBL-1238/1
1/2	12.7	0.020	0.51	SS 316	385	849	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	1.70	3.8	SBL-1251
1/2	12.7	0.020	0.51	SS 304	385	849	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	1.70	3.8	SBL-1251/4
1/2	12.7	0.020	0.51	SS 201	385	849	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	1.70	3.8	SBL-1251/1
1/2	12.7	0.025	0.63	SS 316	453	999	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	2.10	4.6	SBL-1263
1/2	12.7	0.025	0.63	SS 304	453	999	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	2.10	4.6	SBL-1263/4
1/2	12.7	0.025	0.63	SS 201	453	999	SBB-12, SBC-12	30.5 Mtrs (100 Ft.)	2.10	4.6	SBL-1263/1
5/8	15.9	0.015	0.38	SS 316	340	750	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	1.60	3.6	SBL-1538
5/8	15.9	0.015	0.38	SS 304	340	750	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	1.60	3.6	SBL-1538/4
5/8	15.9	0.015	0.38	SS 201	340	750	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	1.60	3.6	SBL-1538/1
5/8	15.9	0.020	0.51	SS 316	453	999	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	2.20	4.8	SBL-1551
5/8	15.9	0.020	0.51	SS 304	453	999	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	2.20	4.8	SBL-1551/4
5/8	15.9	0.020	0.51	SS 201	453	999	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	2.20	4.8	SBL-1551/1
5/8	15.9	0.025	0.63	SS 316	566	1248	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	2.60	5.6	SBL-1563
5/8	15.9	0.025	0.63	SS 304	566	1248	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	2.60	5.6	SBL-1563/4
5/8	15.9	0.025	0.63	SS 201	566	1248	SBB-15, SBC-15	30.5 Mtrs (100 Ft.)	2.60	5.6	SBL-1563/1
3/4	19.0	0.015	0.38	SS 316	408	899	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	2.00	4.4	SBL-1938
3/4	19.0	0.015	0.38	SS 304	408	899	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	2.00	4.4	SBL-1938/4
3/4	19.0	0.015	0.38	SS 201	408	899	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	2.00	4.4	SBL-1938/1
3/4	19.0	0.020	0.51	SS 316	577	1272	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	2.60	5.7	SBL-1951
3/4	19.0	0.020	0.51	SS 304	577	1272	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	2.60	5.7	SBL-1951/4
3/4	19.0	0.020	0.51	SS 201	577	1272	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	2.60	5.7	SBL-1951/1
3/4	19.0	0.025	0.63	SS 316	720	1587	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	3.10	6.8	SBL-1963
3/4	19.0	0.025	0.63	SS 304	720	1587	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	3.10	6.8	SBL-1963/4
3/4	19.0	0.025	0.63	SS 201	720	1587	SBB-19, SBC-19	30.5 Mtrs (100 Ft.)	3.10	6.8	SBL-1963/1