

SS EASY BAND COATED



Application

- Applied where high vibration is the concern



Key Industries

- Aerospace
- Chemicals & Refineries
- Dairy & Food Processing
- Oil, Gas & Offshore
- Ship & Marines
- Signage & Signals
- Solar
- Telecom
- Utility
- Windmill

Specification

- Material:** SS 316
- Coating:** Black PPA - Thermoplastic or Polyester
- Installation:** By tool cat no. TB-1
- Test Certificate:**
- Packing:** 25 Mtrs (82.5 Ft.)/Roll in box

Features

- Ideal for banding & forming any shape pre punch holes make speedy and easy installation with use of nut & bolt
- Coated band provides long term life in corrosive climate condition
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of band provide utmost safety while installation
- Coating material is non-toxic, halogen free, low smoke and UV resistant

Width		Thickness		SS Grade	Hole Dia (Ø)		Package Qty. per Box	G.wt. / Std. Pkg.		Cat. No.
inchs	mm	inches	mm		inches	mm		Kgs.	Lbs.	
1/2	12.7	0.05	1.3	SS 316	3/16	5	25 Mtrs (82.5 Ft.)	1.4	3.1	SBE-12CT
1/2	12.7	0.05	1.3	SS 304	3/16	5	25 Mtrs (82.5 Ft.)	1.4	3.1	SBE-12CT
1/2	12.7	0.05	1.3	SS 201	3/16	5	25 Mtrs (82.5 Ft.)	1.4	3.1	SBE-12CT
3/4	19.0	0.05	1.3	SS 316	9/32	7	25 Mtrs (82.5 Ft.)	2.4	5.3	SBE-17CT
3/4	19.0	0.05	1.3	SS 304	9/32	7	25 Mtrs (82.5 Ft.)	2.4	5.3	SBE-17CT
3/4	19.0	0.05	1.3	SS 201	9/32	7	25 Mtrs (82.5 Ft.)	2.4	5.3	SBE-17CT
1	25.4	0.05	1.3	SS 316	5/16	8	25 Mtrs (82.5 Ft.)	3.3	7.3	SBE-26CT
1	25.4	0.05	1.3	SS 304	5/16	8	25 Mtrs (82.5 Ft.)	3.3	7.3	SBE-26CT
1	25.4	0.05	1.3	SS 201	5/16	8	25 Mtrs (82.5 Ft.)	3.3	7.3	SBE-26CT