

SS EASY BAND UNCOATED

Application

- Suitable for fastening cable, hang ducting & pipes



Key Industries

- Aerospace
- Chemicals & Refineries
- Dairy & Food Processing
- Oil, Gas & Offshore
- Ship & Marines
- Signage & Signals
- Solar
- Telecom
- Utility
- Windmill

Specification

Material:	SS 316
Installation:	By tool cat no. TB-1
Test Certificate:	
Packing:	30.5 Mtrs (100 Ft.)/Roll in box

Features

- Ideal for banding & forming any shape pre punch holes make speedy and easy installation with use of nut & bolt
- Available in cardboard box as well as in plastic totes for easy to carry & use
- Smooth edges of band provide utmost safety while installation

Width		Thickness		SS Grade	Hole Dia (Ø)		Package Qty. per Box	G.wt. / Std. Pkg.		Cat. No.
inchs	mm	inches	mm		inches	mm		Kgs.	Lbs.	
1/2	12.7	0.030	0.76	SS 316	3/16	5	30.5 Mtrs(100 Ft.)	2.80	6.17	SBE-12
1/2	12.7	0.030	0.76	SS 304	3/16	5	30.5 Mtrs(100 Ft.)	2.80	6.17	SBE-12/4
1/2	12.7	0.030	0.76	SS 201	3/16	5	30.5 Mtrs(100 Ft.)	2.80	6.17	SBE-12/1
3/4	19.0	0.030	0.76	SS 316	9/32	7	30.5 Mtrs(100 Ft.)	3.99	8.79	SBE-17
3/4	19.0	0.030	0.76	SS 304	9/32	7	30.5 Mtrs(100 Ft.)	3.99	8.79	SBE-17/4
3/4	19.0	0.030	0.76	SS 201	9/32	7	30.5 Mtrs(100 Ft.)	3.99	8.79	SBE-17/1
1	25.4	0.030	0.76	SS 316	5/16	8	30.5 Mtrs(100 Ft.)	5.36	11.81	SBE-26
1	25.4	0.030	0.76	SS 304	5/16	8	30.5 Mtrs(100 Ft.)	5.36	11.81	SBE-26/4
1	25.4	0.030	0.76	SS 201	5/16	8	30.5 Mtrs(100 Ft.)	5.36	11.81	SBE-26/1