

SS HEAD FOR BALL LOCK BAND UNCOATED



Application

- Designed to be used with SS band ball lock only



Specification

Material: SS 316
Packing: 100 Pcs. bag

Features

- To install ball lock head over the band
- Take one end of the cut length of band & bend 1/2" (13mm) completely from the end of the corner
- Take a self - locking head & slide it over the entire length of the band until it reaches the corner
- Bend tail flat against bottom of banding head to complete assembly

Suitable for Band Width		L Length	W Width	H Height	W1 Width	H 1 Height	SS Grade	Package Qty. per Box	G.wt. / Std. Pkg. (100pcs.)		Cat. No.
inchs	mm	mm	mm	mm	mm	Kgs.			Lbs.		
0.18	4.6	11.50	6.70	4.25	4.70	0.95	SS 316	100 Pcs.	0.10	0.22	SBBLH-4
0.18	4.6	11.50	6.70	4.25	4.70	0.95	SS 304	100 Pcs.	0.10	0.22	SBBLH-4/4
0.18	4.6	11.50	6.70	4.25	4.70	0.95	SS 201	100 Pcs.	0.10	0.22	SBBLH-4/1
0.31	7.9	14.00	9.60	5.30	8.00	0.95	SS 316	100 Pcs.	0.18	0.40	SBBLH-7
0.31	7.9	14.00	9.60	5.30	8.00	0.95	SS 304	100 Pcs.	0.18	0.40	SBBLH-7/4
0.31	7.9	14.00	9.60	5.30	8.00	0.95	SS 201	100 Pcs.	0.18	0.40	SBBLH-7/1
0.50	12.7	16.85	15.63	6.67	14.13	1.26	SS 316	100 Pcs.	0.80	1.76	SBBLH-12
0.50	12.7	16.85	15.63	6.67	14.13	1.26	SS 304	100 Pcs.	0.80	1.76	SBBLH-12/4
0.50	12.7	16.85	15.63	6.67	14.13	1.26	SS 201	100 Pcs.	0.80	1.76	SBBLH-12/1
0.63	15.9	21.23	19.58	8.19	17.69	1.38	SS 316	100 Pcs.	0.89	1.96	SBBLH-15
0.63	15.9	21.23	19.58	8.19	17.69	1.38	SS 304	100 Pcs.	0.89	1.96	SBBLH-15/4
0.63	15.9	21.23	19.58	8.19	17.69	1.38	SS 201	100 Pcs.	0.89	1.96	SBBLH-15/1