

# UV RESISTANT CABLE TIES



## Application

For cable bunching in outdoor weather resistant application

## Key Industries

Telecom • Wind Mill • Solar



## Specification

<b>Material:</b>	Nylon 66
<b>Color:</b>	Black
<b>Operating Temp:</b>	-40°C to 85°C
<b>Flammability Rating:</b>	UL 94V-2
<b>Installation:</b>	By hand or tool cat.no TT-3, TT-4, TT-5
<b>Test Certificate:</b>	UL & CE recognized/ROHS compliance
<b>Packing:</b>	100 pcs bag in all sizes & 1000 pcs. bag upto 200mm length
<b>Unit:</b>	100 Pcs/Pkt & 1000 Pcs/K

## Features

- It is a self locking, non-releasable, economical & versatile method of cable/wire bunching systems
- UV ties are produced from a special grade of UV resistant Nylon6.6 which gives longer years of life span in outdoor climatic condition

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs(lbs)	Maxi. Bundle Dia (mm)	Natural 100 pcs pack Cat No.	Natural 1000 pcs pack Cat No.
75	2.5	1.10	3.0	8 (18)	12	SL-75U	SL-75KU
104	2.5	1.10	4.1	8 (18)	22	SL-100U	SL-100KU
104	2.5	1.10	4.1	12 (27)	22	SL-100XU	SL-100XKU
120	2.5	1.10	4.7	8 (18)	27	SL-120U	SL-120KU
150	2.5	1.10	5.9	8 (18)	35	SL-150U	SL-150KU
200	2.5	1.10	7.9	8 (18)	53	SL-200U	SL-200KU
153	3.6	1.45	6.0	18 (40)	35	SL-150IU	SL-150IKU
153	3.6	1.45	6.0	22 (49)	35	SL-150IXU	SL-150IXKU
204	3.6	1.45	8.0	18 (40)	53	SL-200IU	SL-200IKU
250	3.6	1.45	9.8	18 (40)	68	SL-250IU	
300	3.6	1.45	11.8	18 (40)	80	SL-300IU	
368	3.6	1.45	14.5	18 (40)	104	SL-368IU	
200	4.8	1.50	8.0	30 (67)	53	SL-200SXU	SL-200SXXU
204	4.8	1.50	8.0	22 (49)	53	SL-200SU	
254	4.8	1.50	10.0	22 (49)	68	SL-250SU	
315	4.8	1.50	12.4	22 (49)	86	SL-300SU	
373	4.8	1.50	14.7	22 (49)	104	SL-368SU	
455	4.8	1.50	17.9	22 (49)	130	SL-450SU	
550	4.8	1.50	21.7	22 (49)	165	SL-550SU	
206	7.8	1.80	8.1	54 (119)	53	SL-200HU	
256	7.8	1.80	10.1	54 (119)	68	SL-250HU	
312	7.8	1.80	12.3	54 (119)	82	SL-300HU	
382	7.8	1.80	15.0	54 (119)	105	SL-380HU	
453	8.1	1.95	17.8	54 (119)	130	SL-450HU	
551	9.1	2.00	21.7	81 (180)	163	SL-550HU	
616	9.1	2.00	24.3	81 (180)	180	SL-610HU	
716	9.1	2.00	28.2	81 (180)	210	SL-710HU	
816	9.1	2.00	32.1	81 (180)	240	SL-810HU	
916	9.1	2.00	36.1	81 (180)	276	SL-910HU	
1016	9.1	2.00	40.0	81 (180)	305	SL-1010HU	

**Tolerance Dimension (mm):** Length -  $\pm 1$  to 5, Width -  $\pm 0.3$  to 0.4, Thickness -  $\pm 0.2$  to 0.4