

# UV RESISTANT METAL TOOTH TIES

## Application

- For outdoor cable bunching
- For durable locking in the adverse conditions like humidity, heat, cold, vibration & external shocks



## Key Industries

Aviation • Locomotive • Windmill

## Specification

<b>Material:</b>	Nylon 66
<b>Color:</b>	Black
<b>Operating Temp:</b>	-40°C to +85°C
<b>Flammability Rating:</b>	UL 94V-2
<b>Installation:</b>	By hand or tool cat no. TT-3, TT-4, TT-5
<b>Test Certificate:</b>	UL & CE recognized/ROHS compliance
<b>Packing:</b>	100 pcs bag in all sizes
<b>Unit:</b>	100 Pcs/Pkt

## Features

- UV metal Tooth ties are produced from special grade of UV resistant Nylon6.6 which provides longer life span in outdoor weather condition
- The corrosion proof, non magnetic steel tooth firmly anchor inside the cable tie length (body) with positive locking
- No chances of slippage in adverse conditions

Length (mm)	Width (mm)	Thickness (mm)	Length (inch)	Tensile Strength Kgs (lbs)	Maxi. Bundle Dia (mm)	CAT No.
100	2.5	1.0	4.0	8 (18)	22	SLM-100U
200	2.5	1.0	8.0	8 (18)	50	SLM-200U
150	3.6	1.1	6.0	18 (40)	30	SLM-150IU
200	3.6	1.1	8.0	18 (40)	50	SLM-200IU
280	3.6	1.1	11.0	18 (40)	76	SLM-280IU
200	4.8	1.1	8.0	22 (49)	50	SLM-200SU
290	4.8	1.1	11.4	22 (49)	78	SLM-290SU
360	4.8	1.1	14.2	22 (49)	102	SLM-360SU
220	7.6	1.6	8.6	54 (119)	57	SLM-220HU
300	7.6	1.6	11.8	54 (119)	80	SLM-300HU
368	7.6	1.6	14.5	54 (119)	102	SLM-368HU
538	7.6	1.6	21.2	54 (119)	158	SLM-538HU
780	7.6	1.6	30.7	54 (119)	230	SLM-780HU

**Tolerance Dimension (mm):** Length -  $\pm 1$  to 4, Width -  $\pm 0.2$  to 0.4, Thickness -  $\pm 0.2$  to 0.4